


Roadway Typical Sections




TYPICAL "B"

No Scale

130 / R

TYPICAL SECTION VERTICAL ROUTE MARKER




Letters shall be 4" white reflective, Series "C"
on Brown 6" 6" Carsonite Post or equal CMR375

Figure 11-28.- Typical Signage for Vertical Route Markers


TYPICAL "F"

No Scale

TYPICAL APPROACH ROAD CONNECTION



*As noted on
road sheets



Fill slopes are
V1 H1.5 (1.5:1)
or as staked

Ditch width shall be the larger of the following:

- A. Standard ditch width
- B. 2 times the pipe diameter
- C. 4.25'

Ditch depth shall be:	
CMP diameter	Ditch depth
18"	2.5'
24"	3.0'
36"	4.0'
48"	5.0'

Back slopes are
V1 H1 (1:1) or
as staked

Confidentiality Notice:
The information contained on this plot is legally privileged and confidential information intended only for the use of recipients. If you are not the intended recipients, you are hereby notified that any use, dissemination, distribution or copying of this information is strictly prohibited.

TYPICAL "A"

No Scale

Drawn By J.U./R.K.C.	Surveyed By Nick Jensen	Approved By M. J. Kadrmas	Scale None	Date 2/9/2011
Field Book OW-245	Material Road Typical	Revised 4/4/2011	Project No. 3711157	Drawing No. 6

**Kadrmas
Lee &
Jackson**
Engineers Surveyors
Planners